

Spare part SIMATIC S7-200, analog I/O EM 235, only for S7-22X CPU, 4 AI, +/-10 V DC; 1 AO, +/-10 V DC 12 bit converter



Input current	
from external supply (24 V DC), max.	60 mA
from backplane bus 5 V DC, max.	30 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	4; Difference
permissible input voltage for voltage input (destruction limit), max.	30 V
permissible input current for current input (destruction limit), max.	32 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	

• 0 to +50 mV	Yes
• 0 to +100 mV	Yes
• 0 to +500 mV	Yes
• 0 to +1 V	Yes
• 0 to +5 V	Yes
• 0 to +10 V	Yes
• -1 V to +1 V	Yes
• -10 V to +10 V	Yes
• -100 mV to +100 mV	Yes
• -2.5 V to +2.5 V	Yes
• -25 mV to +25 mV	Yes
• -250 mV to +250 mV	Yes
• -5 V to +5 V	Yes
• -50 mV to +50 mV	Yes
• -500 mV to +500 mV	Yes
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Analog outputs	
Number of analog outputs	1
Output ranges, voltage	
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	5 k Ω
• with current outputs, max.	0.5 k Ω
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit
• Basic conversion time (ms)	< 0.25 ms
• Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 Hz
Displayable conversion value range	
• bipolar signals	-32 000 to +32 000
• unipolar signals	0 to 32 000
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	

• Resolution with overrange (bit including sign), max.	11 bit
Settling time	
• for voltage output	100 µs
• for current output	2 ms
Displayable conversion value range	
• bipolar signals	-32 000 to +32 000
• unipolar signals	0 to 32 000
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	2 %
• Current, relative to output range, (+/-)	2 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.5 %
• Current, relative to output range, (+/-)	0.5 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Common mode voltage, max.	12 V
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• external fault EXTf (red)	Yes
Potential separation	
Potential separation analog inputs	
• Potential separation analog inputs	No
Potential separation analog outputs	
• Potential separation analog outputs	No
Connection method	
Plug-in I/O terminals	No
Dimensions	
Width	71.2 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	186 g
last modified:	11/28/2020