

PRODUCT-DETAILS

A110-30-11-80

A110-30-11 220-230V 50Hz / 230-240V 60Hz

Contacteur



General Information

Extended Product Type	A110-30-11-80
Product ID	1SFL451001R8011
EAN	7320500141595
Catalog Description	A110-30-11 220-230V 50Hz / 230-240V 60Hz Contacteur
Long Description	A 3-phase Contacteur suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 1000 V. Operated with control voltage, versions from 24V AC, 50 and 60 Hz

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	162 mm
Package Level 1 Gross Weight	2 kg
Package Level 1 EAN	7320500141595

Certificates and Declarations (Document Number)

BV Certificate	07172/D0 BV
CB Certificate	SE-69487
CCC Certificate	CQC_2002010304008904
CSA Certificate	314005
Declaration of Conformity - CE	2CMT2015-005436
DNV Certificate	DNV_E-12191
Environmental Information	1SFC101001D0201
GL Certificate	GL_99358-97HH
Instructions and Manuals	5309660-60
LOVAG Certificate	SE-9645071-2
LR Certificate	LR_12-70027-E1
RINA Certificate	ELE060313XG/001
RMRS Certificate	RMRS_12-03683-315
RoHS Information	2CMT2015-005436

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 140 A
Horsepower Rating UL/CSA	(200 V AC) Three Phase 30 hp (208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 40 hp (440 ... 480 V AC) Three Phase 75 hp (550 ... 600 V AC) Three Phase 100 hp

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... +50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 K40 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 K40 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 10 K40

Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock
 Direction: C1 20 K40
 Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock
 Direction: C2 20 K40
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock
 Direction: B1 5 K40
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock
 Direction: B2 15 K40
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock
 Direction: C1 20 K40
 Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock
 Direction: C2 20 K40

RoHS Status Following EU Directive 2011/65/EU

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ }^{\circ}\text{C}$ 160 A
Rated Operational Current AC-1 (I_e)	(690 V) $40\text{ }^{\circ}\text{C}$ 160 A (690 V) $55\text{ }^{\circ}\text{C}$ 145 A (690 V) $70\text{ }^{\circ}\text{C}$ 130 A
Rated Operational Current AC-3 (I_e)	(1000 V) $55\text{ }^{\circ}\text{C}$ 30 A (220 / 230 / 240 V) $55\text{ }^{\circ}\text{C}$ 110 A (380 / 400 V) $55\text{ }^{\circ}\text{C}$ 110 A (415 V) $55\text{ }^{\circ}\text{C}$ 110 A (440 V) $55\text{ }^{\circ}\text{C}$ 100 A (500 V) $55\text{ }^{\circ}\text{C}$ 100 A (690 V) $55\text{ }^{\circ}\text{C}$ 82 A
Rated Operational Power AC-3 (P_e)	(1000 V) 40 kW (220 / 230 / 240 V) 30 kW (380 / 400 V) 55 kW (415 V) 59 kW (440 V) 59 kW (500 V) 59 kW (690 V) 75 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 200 A
Rated Short-time Withstand Current (I_{cw})	at $40\text{ }^{\circ}\text{C}$ Ambient Temp, in Free Air, from a Cold State 10 s 800 A at $40\text{ }^{\circ}\text{C}$ Ambient Temp, in Free Air, from a Cold State 15 min 175 A at $40\text{ }^{\circ}\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 min 350 A at $40\text{ }^{\circ}\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at $40\text{ }^{\circ}\text{C}$ Ambient Temp, in Free Air, from a Cold State 30 s 500 A
Maximum Breaking Capacity	$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 440 V 1160 A $\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 690 V 800 A
Maximum Electrical	AC-1 300 cycles per hour

Switching Frequency	AC-2 / AC-4 150 cycles per hour AC-3 300 cycles per hour
Rated Operational Current DC-1 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Operational Current DC-3 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Operational Current DC-5 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 15 ms Between Coil De-energization and NO Contact Opening 10 ... 18 ms Between Coil Energization and NC Contact Opening 7 ... 22 ms Between Coil Energization and NO Contact Closing 10 ... 25 ms
Connecting Capacity Main Circuit	Bar 30 mm ² Flexible with Cable End 2 x 6 ... 35 mm ² Rigid 1 x 10 ... 95 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 1x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M8 hexagon socket screw with single connector
Terminal Type	Cable Clamp

Dimensions

Product Net Width	102 mm
Product Net Depth / Length	123.5 mm
Product Net Height	148 mm
Product Net Weight	1.8 kg

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	5309660-60
Dimension Diagram	53540923-1

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SFL427001R1311

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

Robotics → Robots → Articulated Robots → IRB 6400

